

## Product Highlights

### Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions

### Reduced maintenance costs

- Exclusive open chassis design reduces daily maintenance costs
- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

### More reliable performance

- New wide scissor design, for a more stable working-at-height experience
- Bumper rail and indented sliding groove designed for anti-scratch

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		


# SINOBOOM

Sinoboom Intelligent Equipment Co Ltd

📍 No.128 East Jinzhou Av., Ningxiang Hi-Tech Industry Park, Changsha, Hunan, China, 410600

🌐 [www.sinoboom.com](http://www.sinoboom.com)

✉ [sales@sinoboom.com](mailto:sales@sinoboom.com)



Model	
Dimensions	
Max Working Height	
A	Max Platform Height
B	Max Horizontal Extension
C	Length-Stowed
D	Width-Stowed
Height - stowed	Rail Folded
	E Rail Unfolded
F Wheelbase	
Ground Clearance (Pothole Guard Stowed)	
Ground Clearance (Pothole Guard Deployed)	
Platform Dimensions(LxWxH)	
Performance	
Platform Allowable Occupants (Indoor/ Outdoor)	
Platform Capacity	
Drive Speed-Stowed	
Drive Speed-Raised	
Elevation Time(Unloaded)	
Descent Time(Unloaded)	
Gradeability	
Turning Radius (Inside/Outside)	
Tilt Rating (Front to Back/Side to Side)	
Tyres-solid	
Power	
Batteries	
Power Source	
Drive Mode	
Charger Input	
Charger Output	
Hydraulic System Capacity	
Weight	
Weight(Indoor/Outdoor)	
Weight(Indoor Only)	
Standards Compliance	

1012E (3346E)	
Metric	US
12m	39'4.5"
10m	32'10"
0.9m	3'
2.45m	8'
1.17m	3'10"
1.86m	6'1"
2.48m	8'2"
1.88m	6'2"
0.1m	4"
25mm	0.98"
2.30m×1.15m×1.1m (7'6.5"×3'9"×3'7")	
2 persons/1 person	
320kg	705.6lbs
4km/h	2.5mph
0.8km/h	0.5mph
53s~58s	
40s~45s	
25%	
0/2.35m	0/7'8.5"
3°/1.5°	
380×125mm	15×5"
6V×4/240Ah	
24V DC	
Motor, front-wheel	
100~240V AC	
30A	
34L	7.5gal
2,815kg	
6,206lbs	
2,645kg	
5,831lbs	
TR/KCS	

